

BT Printer Combo Adapter (BT-PTR)



Features:

- Support Bluetooth Hard Copy Replacement Printing Profile (HCRP)
- Support Bluetooth Serial Port Profile (SPP)
- Support Bluetooth v2.0+EDR
- Operate in 2.4GHz~2.483GHz ISM band
- Bluetooth Class I
- Operating distance of up to 100 meters
- Support both USB and 1284 printer port interfaces
- Three LEDs Indicating: Power On/Off, Printer Action, Bluetooth Link
- Easy operation and setup

Specifications:

Standard	Bluetooth v2.0+EDR
Frequency Band	2.4~2.4835GHz unlicensed ISM band
Spread Spectrum	FHSS (Frequency Hopping Spread Spectrum)
Services supported	SPP and HCRP print services
RF Output Power	Class 1; 13dBm typical
Working distance	Up to 100m in free space
Sensitivity	<-88dBm at < 0.1% BER
I/O Interface	USB, IEEE-1284
LED indicator	Power / Bluetooth active /Printing active
Environment	Operation temperature: 0 ~ + 60 C Degree
	Storage temperature: -10 ~ +70 C Degree
	Humidity: 5 ~ 90% non-condensing
Dimension	76 (L) x 62(W) x 20(H) mm

Remark: All contents are subject to change without notice



Ubiquitous Connect

UConnect International CO., LTD.

Address: 13F., No.368, Sec. 1, Fuxing S. Rd., Taipei City 106, Taiwan (R.O.C.)
Tel: +886-2-23250518
Fax: +886-2-23250627
E-Mail: Sales@uconnect.com.tw
Web: www.uconnect.com.tw